



X-Charge eXpress Link

The X-Charge program can be started with the defaults set for each field for a defined transaction type. This is useful if X-Charge will be started from another program and certain fields, such as amount, clerk, ZIP, address, etc., are already known. An option also exists to automatically close X-Charge after a successful transaction is complete. These options only work when X-Charge is started with no other copies of X-Charge already running. If X-Charge is already running the default values will not be set.

```
XCharge.exe [/TRANSACTIONTYPE:type] [/AMOUNT:amount] [/ACCOUNT:account] [/EXP:exp]
[/"TRACK:track"/] [/ZIP:zip] [/ADDRESS:address] [/RECEIPT:receipt] [/CLERK:clerk]
[/APPROVALCODE:approval] [/AUTOPROCESS] [/AUTOCLOSE] [/STAYONTOP] [/MID]
[/RESULTFILE:"C:\Program Files\X-Charge\LocalTran\XCResult.txt"]
```

/TRANSACTIONTYPE

Default transaction type. PURCHASE (if no transaction type specified)
Transactiontype = PURCHASE, RETURN, DEBITPURCHASE, DEBITRETURN, FORCE,
PREAUTH, GIFTISSUE, GIFTREDEEM, GIFTRETURN, GIFTBALANCEINQUIRY
Example: /TRANSACTIONTYPE:PURCHASE

/LOCKTRANTYPE

The transaction type set by the /TRANSACTIONTYPE option is set as the only transaction type available to the user
Example: /LOCKTRANTYPE

/LOCKTRANTYPEGROUP

The transaction type set by the /TRANSACTIONTYPE option, and other similar transaction types, are set as the only transaction types available to the user. For example, if PURCHASE is set as the transaction type, then the user will have access to the Purchase, Debit Purchase, Force, and Gift Redeem transactions. If RETURN is set as the transaction type then the user will have access to Return, Debit Return, and Gift Return.
Example: /LOCKTRANTYPEGROUP

/AMOUNT

Amount in #.## format.
Example: /AMOUNT:12.34

/TRACK

Credit card track data. The quotes are necessary since track information may have spaces. This option overrides any /ACCOUNT and /EXP information.
Example: "/TRACK::;5499990123456781=09081015432198712345?"

/ACCOUNT

Credit card or gift card account number.
Example: /ACCOUNT:5499990123456781

/EXP

Expiration in MMY format.
Example: /EXP:0809



/ZIP

ZIP code

Example: /ZIP:83642

/ADDRESS

Street Address

Example: /ADDRESS:1874 EAGLE DR

Note: If there are spaces in the address, or any command line parameter, the entire parameter must be enclosed in quotes. Example: "/ADDRESS:1874 EAGLE DR"

/RECEIPT

Sales receipt/invoice number

Example: /RECEIPT:001

/CLERK

Sales clerk/associate

Example: /CLERK:JERRY

/APPROVALCODE

Approval Code

Example: /APPROVALCODE:123456

/AUTOPROCESS

Auto processes the transaction.

Example: /AUTOPROCESS

Note: If the transaction information is invalid, such as an invalid account number or missing amount, the processing will not continue and user will be prompted for correct information.

/AUTOCLOSE

Auto close program after transaction

Example: /AUTOCLOSE

/RESULTFILE

If the /AUTOCLOSE option exists, a result text file will be created

Example: /RESULTFILE:C:\X-Charge\XResult.txt (If spaces, encapsulate the file name in quotes: "C:\Program Files\X-Charge\XCResult.txt")

Example file for a successful transaction:

RESULT=SUCCESS
TYPE=Purchase
APPROVALCODE=000064
ACCOUNT=XXXXXXXXXXXX6781
ACCOUNTTYPE=VISA*
AMOUNT=1.77
AVSRESULT=Y
CVRESULT=M

* ACCOUNTTYPE = MasterCard, VISA, American Express, Diners Club, Discover, JCB

Example file for a declined or failed transaction:

RESULT=Transaction not completed



/STAYONTOP

The X-Charge program is configured to always stay on top of the other windows and the minimize button is disabled.

Example: /STAYONTOP

/MID

MerchantID

Example: /MID:223496